

## CLAIMS

**Claim 1 (Currently Amended)** A method for driving a plasma display panel having a scan electrode, a sustain electrode and a data electrode forming a discharge cell at a point of intersection therebetween, said method for driving the plasma display panel comprising:

~~an initialization period for forming a discharge cell at an intersection where a scan electrode and a sustain electrode meet a data electrode and~~

generating, during an initialization period, an initialization discharge in the discharge cell;~~a~~

generating, during a writing period, for generating a writing discharge in the discharge cell; ~~and, and~~

generating, during a sustain period, for generating a sustain discharge by alternately applying sustain pulses to the scan electrode and sustain electrode of the discharge cell,

wherein a rise time of the a sustain pulse-pulses to be applied to the scan electrode during the sustain period is shortened at a frequency of once every three times a sustain pulse is applied thereto,

wherein-and a rise time of a sustain pulse applied to the sustain electrode during the sustain period is shortened at a frequency of once every three times a sustain pulse is applied thereto, and

wherein sustain pulses, applied to the scan electrode and the sustain electrode between the sustain pulses having the shortened rise time, have a non-shortened rise time that is longer than the shortened rise time-plural times.

**Claim 2 (Cancelled)**

**Claim 3 (New)**        A method for driving a plasma display panel having a scan electrode, a sustain electrode and a data electrode forming a discharge cell at a point of intersection therebetween, said method for driving the plasma display panel comprising:

generating, during an initialization period, an initialization discharge in the discharge cell;

generating, during a writing period, a writing discharge in the discharge cell; and

generating, during a sustain period, a sustain discharge by alternately applying sustain pulses to the scan electrode and sustain electrode of the discharge cell,

wherein a rise time of a sustain pulse applied to the scan electrode during the sustain period is shortened at a frequency of one of (i) once every two times and (ii) once every three times, a sustain pulse is applied thereto,

wherein a rise time of a sustain pulse applied to the sustain electrode during the sustain period is shortened at a frequency of one of (i) once every two times and (ii) once every three times, a sustain pulse is applied thereto, and

wherein sustain pulses, applied to the scan electrode and the sustain electrode between the sustain pulses having the shortened rise time, have a non-shortened rise time that is longer than the shortened rise time.

**Claim 4 (New)**        The method of driving a plasma display panel according to claim 1, wherein a time delay exists between applying the sustain pulse having the shortened rise time to

the scan electrode and applying the sustain pulse having the shortened rise time to the sustain electrode, the time delay causing the sustain pulse having the shortened rise time to be applied to the sustain electrode only after a falling edge of the sustain pulse having the shortened rise time has occurred on the scan electrode and a rising edge of a sustain pulse having a non-shortened rise time has occurred on the scan electrode.